

WMS

Manual Fork Over Stacker

Ideal and standard series for manual transport and lifting, with its different mast options and diverse lifting capacity enables to deal with a large number of applications in the warehouse or any other facilities.

- ◆ Optional choice of fixed bended fork (560/685X1150mm).
- ◆ Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller.
- ◆ We can offer additional protection for the operator through foot protection on the steering rollers.



- ◆ Safe parking in any situation with mechanical parking brake.
- ◆ Optional tiller pumping lifting and foot pedal lifting.



SPECIFICATIONS

MODEL		WMS500-1600				WMS1000				WMS1500				WMS2000-1600			
FEATURE		Q kg		500		1000		1500		2000		2500		3000		1600	
1.1	Capacity	Q kg		500		1000		1500		2000		2500		3000		1600	
1.2	Load Center	C mm		500		500		500		500		500		500		500	
DIMENSIONS		h mm		1600		1600		2000		2500		3000		1600		1600	
2.1	Lifting height	h mm		1600		1600		2000		2500		3000		1600		1600	
2.2	Mast lowered height	H mm		1970		2020		1500		1770		2020		2070		1500	
2.3	Mast extend height	H1 mm		1970		2020		2510		3010		3510		2070		2510	
2.4	Mast type	S		S		S		D		D		D		D		S	
2.5	Lowered height of fork	h1 mm		95		95		90		90		90		90		90	
2.6	Fixed fork outside distance	W mm		560		680		560		680		560		680		560	
2.7	Option Adjustable fork, adjustable range	mm		230-870		230-680		230-870		230-680		230-870		230-680		230-870	
2.8	Fork length	slell mm		1150		1150		1150		1150		1150		1150		1150	
2.9	Overall width	W2 mm		780		780		870		870		870		870		780	
2.10	Overall length	L mm		1650		1650		1650		1650		1650		1650		1650	
2.11	Lifting speed	mm/time		≥16		≥16		≥16		≥16		≥16		≥16		≥16	
2.12	Lowering speed			Controllable		Controllable		Controllable		Controllable		Controllable		Controllable		Controllable	
2.13	Turing Radius	Wr mm		1590		1590		1600		1600		1590		1600		1600	
WHEEL		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon	
3.1	wheel(drive/load) Type	PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon		PU/Nylon	
3.2	size of steering wheel	∅D mm		∅180*50		∅180*50		∅180*50		∅180*50		∅180*50		∅180*50		∅180*50	
3.3	size of Loading wheel	∅d mm		∅80*60		∅80*60		∅80*60		∅80*60		∅80*60		∅80*60		∅80*60	
3.4	service weight	kg		160		187		260		280		298		211		270	

